



201 East Pleasant Street
Maquoketa, IA 52060-3050
E-mail: maqcity@maquoketaia.com

Phone: (563) 652-2484
Fax: (563) 652-2485
www.maquoketaia.com

Sidewalk Concrete Program Program Rules City of Maquoketa

The City of Maquoketa has created a "Sidewalk Concrete Program." The City will provide funds to pay toward the cost of concrete and provide concrete forms for property owners who wish to either repair/reconstruct existing public sidewalks or install new public sidewalks.

This program is applicable for both *residential* and *commercial* property. Property owners are responsible for providing the labor. Further program guidelines are as follows:

- 1.) All applications must be approved by the Public Works Director (563-652-4628) or his designee before any work can begin.
- 2.) All sidewalk work must be done according to the attached "Sidewalk Construction Standards."
- 3.) The City reserves the right to limit its participation in projects due to factors such as, but not limited to: budgetary constraints; whether or not a sidewalk is on a key walking route; the extent to which a sidewalk is cracked, broken-up, or missing; or other factors. Also, the City's involvement in non-residential sidewalks is limited to no more than \$500.
- 4.) Property owners may use the City's concrete forms at no charge. However, forms must be cleaned and oiled upon their return to the City. If forms are not properly cared for, the City may assess a penalty of \$50. Should any property owner not pay any amount that is billed, that amount and any administrative costs may be applied to his/her property taxes.
- 5.) The completed project must be approved by the Public Works Director.
- 6.) Upon this approval, the property owner may submit his/her itemized bill for the cost of the concrete needed for the project. The City will reimburse a property owner for the lesser of his/her cost of concrete or the amount of what the concrete would have cost the City if the City had done the project at the City's bid price for a 4 foot wide, 4 inch thick sidewalk without any additives, rebar, trucking/delivery charges, or other extras.
- 7.) The City reserves the right to change the rules of this program at any time.

Questions about the Program Rules may be directed to Maquoketa City Hall at 563-652-2484.

Questions about sidewalk repair or construction methods may be directed to the Public Works Director at 563-652-4628.

**Information on Sidewalk Construction Standards
City of Maquoketa**

These standards must be followed when repairing or constructing City sidewalks:

- 1.) Concrete. Air-entrained Portland cement with a minimum 4,000 PSI shall be used in the construction and repair of sidewalks.
- 2.) Construction. Sidewalks shall be of one-course construction.
- 3.) Sidewalk Base. Concrete may be placed directly on compacted and well-drained soil. Where soil is not well drained, a three (3) inch sub-base of compact, clean, coarse gravel, sand, or cinders shall be laid. The adequacy of the soil drainage is to be determined by the Building Official.
- 4.) Joint Filler. A one-half (1/2) inch non-extruding type expansion joint shall be provided between all sidewalks and adjoining backs of curbs and between intersecting sidewalks and between sidewalks and driveways.
- 5.) Sidewalk Bed. The sidewalk bed shall be so graded that the constructed sidewalk will be at established grade.
- 6.) Valves Boxes and Manholes. All water valve boxes and manholes shall be adjusted flush with the sidewalk.
- 7.) Length, Width and Depth. Length, width and depth requirements are as follows:
 - a.) Residential sidewalks shall be at least four (4) feet wide and four (4) inches thick, and each section shall normally be scored at four (4) foot intervals, but in no case more than six (6) foot intervals.
 - b.) Central Business District sidewalks shall extend from the property line to the curb. Each section shall be not less than four (4) inches thick and, at a minimum, shall match the width of existing commercial sidewalks being replaced.
 - c.) Driveway areas shall be not less than four (4) inches thick for residential applications and not less than six (6) inches in thickness for all other applications including alley crossings.
 - d.) In areas where sidewalks are something other than 4 feet wide on both sides of a sidewalk meant for reconstruction or replacement, the width of the reconstructed/replaced area may match the existing sidewalks in the immediate area. In situations where a new sidewalk takes off from the end of an existing sidewalk of less than 4 feet in width, the new sidewalk must be at least 4 feet in width.
- 8.) Location.
 - a.) Residential sidewalks shall be located with the inner edge (edge nearest the abutting private property) one (1) foot from the property line, unless the City establishes a different distance due to circumstances such as for the preservation of existing trees.
 - b.) Utility companies contemplating the installation of their infrastructure shall not create conflicts or obstacles to the placement of future sidewalks or the reconstruction or maintenance of existing sidewalks. This also applies to streets where sidewalks do not currently exist.
- 9.) Grade. Curb tops shall be on level with the correct centerline of the street which shall be at the established grade.
- 10.) Elevations. The street edge of a sidewalk shall be at an elevation even with the curb at the curb where sidewalks adjoin the curb and one-half (1/2) inch above the curb for each foot between the curb and the sidewalk elsewhere.
- 11.) Slope. All sidewalks shall slope one-quarter (1/4) inch per foot toward the curb.
- 12.) Finish. All sidewalks shall be finished with a "broom" finish to provide a non-skid surface.
- 13.) Curb Ramps for Persons with Disabilities. If a street, road, or highway is newly built or reconstructed, a curb ramp or sloped area shall be constructed or installed at each intersection of the street, road, or highway with a sidewalk or path. If a sidewalk or path is newly built or reconstructed, a curb ramp or sloped area shall be constructed or installed at each intersection of the sidewalk or path with a street, highway, or road. Curb ramps and sloped areas that are required pursuant to this subsection shall be constructed or installed in compliance with applicable Federal requirements adopted in accordance with the Federal Americans with Disabilities Act, including (but not limited to) the guidelines issued by the Federal Architectural and Transportation Barriers Compliance Board. (Code of Iowa, Sec. 216C.9)
[The City will be responsible for the construction of curb ramps, in particular, at corner lots.]
- 14.) Maintenance and Repairs. The following is permitted:
 - a.) Grinding may be done to even-out heaved-up sidewalk squares or panels if it results in a compliant sidewalk.

Further:

- Patching material shall not be used to repair defective sidewalks.
- New public sidewalks require a building permit.
- The City's "Sidewalk Concrete Program" is available to partially assist in the cost of your sidewalk project.
- For more information or guidance on how to construct sidewalks or make repairs, please contact: Frank Ellenz, Public Works Director, 563-652-4628.

Sidewalk Concrete Program Application.

1.) Name(s)/Phone #: _____

2.) Address for which you are applying: _____

3.) In feet, what is the length of proposed sidewalk work: _____

4.) Did you receive a "Sidewalk Inspection Report" informing you of the need to make sidewalk repairs?
_____ yes _____ no

5.) Describe the problem with the public sidewalk for which you are applying. For example, is it missing, cracked, a trip hazard, etc? Please note if the problem involves a "City tree." Or, if you received a copy of a "Sidewalk Inspection Report," you may also refer to it.

Property Owner's Agreement:

I am an applicant to the City of Maquoketa's "Sidewalk Concrete Program." I have read, understand, and agree to the rules and obligations of the program.

Signature(s) and Date: _____

+++++
{Office Use Only}

Determination by the City on this application:

